Patent Application Attorney Docket No. 18405-115

Express Mail Label No.: EV326601442US Date of Deposit: January 28, 2005

Listing of the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the

application:

1. (currently amended) A multiple sample processing apparatus for a continuous flow

centrifuge, comprising a plurality of axially aligned processing chambers and expressor

chambers, each chamber including an axial opening housing a central hub, wherein a

respective central hub of a respective chamber includes at least one first axially aligned

dedicated passageway aligned substantially parallel to a central axis of the hub

dedicated for fluid communication with a first chamber and at least one second axially

aligned dedicated passageway aligned substantially parallel to the central axis of the

huh for fluid communication with a second chamber.

2. (original) The apparatus according to claim 1, wherein said processing chambers and

said expressor chambers are alternately arranged.

3. (original) The apparatus according to claim 1, wherein each said processing chamber is

arranged within a corresponding expressor chamber.

4. (original) The apparatus of claim 1, wherein the processing and expressor chambers are

constructed and arranged to be flexible and expandable.

5. (original) The apparatus of claim 1, wherein the processing and expressor chambers are

constructed and arranged to releasably contact each other at a circumferential portion of

the chambers when the expressor chambers are filled with an expressor fluid.

6. (original) The apparatus of claim 5, wherein the central hubs are constructed and

arranged to prevent construction of an apparatus having two adjacent processing

chambers.

7. (original) The apparatus of claim 6, wherein the central hubs are constructed and

- 3 -

Patent Application Attorney Docket No. 18405-115

Express Mail Label No.: EV326601442US Date of Deposit: January 28, 2005

arranged to prevent construction of an apparatus having two adjacent expressor chambers.

- 8. (original) The apparatus of claim 1, wherein the central hubs are constructed and arranged to define multiple passages for fluid communication.
- 9. (original) The apparatus of claim 8, wherein the central hubs comprise a number of passages for fluid communication that is at least equal to the number of chambers in the apparatus.
- 10. (original) The apparatus of claim l, further comprising a plurality of weld rings disposed on the central hubs, and constructed and arranged to permit attachment of processing chambers and expressor chambers.
- 11. (original) The apparatus of claim l, wherein the processing chambers and expressor chambers are substantially the same shape.
- 12. (original) The apparatus of claim l, wherein the processing chambers are smaller then the expressor chambers.
- 13. (original) The apparatus of claim 11, wherein the processing chambers and expressor chambers are substantially circular.
- 14. (previously amended) The apparatus of claim 13, wherein the processing chambers and expressor chambers have substantially the same diameter.
- 15. (original) The apparatus of claim 12, wherein the processing chambers have a smaller diameter than the expressor chambers.
- 16. (original) The apparatus of claim 1, wherein the processing chambers and expressor chambers are constructed from two sheets of flexible material, the two sheets of material sealed at an outer circumference and an inner circumference, wherein the inner circumference is substantially adjacent the axial opening.

Patent Application Attorney Docket No. 18405-115

Express Mail Label No.: EV326601442US Date of Deposit: January 28, 2005

- 17. (Canceled).
- 18. (original) The apparatus of claim l, further comprising a fluid entry hub disposed at a fluid entry point of the plurality of axially aligned processing chambers and expressor chambers, the fluid entry hub being constructed and arranged to serve as an interface for fluid communication between the plurality of axially aligned alternating processing chambers and expressor chambers and a fluid pathway external to the continuous flow centrifuge.
- 19. (original) The apparatus of claim 18, wherein the fluid pathway is a multi-lumen tube.
- 20-34. (previously canceled).
- 35. (currently amended) A multiple sample processing apparatus for a continuous flow centrifuge, comprising a plurality of axially aligned processing chambers, each chamber including an axial opening housing a central hub, wherein a respective central hub of a respective chamber includes at least one first axially aligned dedicated passageway aligned substantially parallel to a central axis of the hub dedicated for fluid communication with a first chamber and at least one second dedicated passageway aligned substantially parallel to the central axis of the hub for fluid communication with a second chamber.
- 36. (currently amended) A multiple sample processing apparatus for a continuous flow centrifuge, comprising at least one processing chamber and at least one axially aligned expressor chamber, each chamber including an axial opening housing a central hub, wherein a respective central hub of a respective chamber includes at least one first axially aligned dedicated passageway aligned substantially parallel to a central axis of the hub dedicated for fluid communication with a first chamber and at least one second axially aligned dedicated passageway aligned substantially parallel to the central axis of the hub for fluid communication with a second chamber.